


ver. 20200404 Rev 0

year: **2022**

code: 2730373S20000

type: hanging lamp


application: **indoor**



## Technical drawing

Size

ref. image mm - inch



## Technical data

Light source	LED
Circuit structure	LED strip
Light emission direction	diffused
Power	153 W
Source lumens	21420 lm
Source efficacy	140 lm/W
Consumption	171 W
Delivered lumens	14193 lm
Luminaire efficacy	83 lm/W
Secondary	24 V
Colour temperature	3000 K / variants page 2
Colour rendering index	80 CRI / variants page 2
Standard Deviation of Colour Matching	3 SDCM
Energy class	A
Safety class	I
Degree of protection	IP 20
Direct mounting on normally flammable surfaces	●
Operating temperature	+10° / +40°
CE	●
UL	●

## Optional

Emergency mode	ⓘ
Motion sensor	ⓘ
Directional	ⓘ

## Packing

Net weight	
Packaging 1	L1610 x W1620 x H130 mm / 14.6 kg
Packaging 2	
Packaging 3	
Packaging 4	
Packaging 5	

## Structure

Material	aluminium
Finish	white / variants page 2

## Diffuser

Material	polycarbonate
Finish	opal / variants page 2

## Canopy

Size	240 mm - 9" 1/2 inch
Height	57 mm - 2" 1/4 inch
Ceiling mount	perpendicular / variants page 2

## Electronics / Driver

Included	Yes
Quantity	2
Voltage	100-277V 50/60 Hz

**Dimmable**



### Hanging cables

Stainless steel cables standard length (custom available)	2000 mm / 78" 3/4
Electric cable standard length (custom available)	2500 mm/100"

## Warranty

Duration	2 years
----------	---------

# CIRCUS round vertical S2000 v2 1-10V 100-277V

ver. 20200404\_Rev\_0

year: **2022**

code: **2730373S20000**

type: **hanging lamp**

application: **indoor**

## Available variants

### Colour temperature

2700 k



3000 k



3500 k



4000 k



custom



### Colour rendering index

CRI 80



CRI 90



CRI 95



custom



### Structure finish

gold / brass



matt white



matt black



embossed white



embossed black



custom



### Diffuser / Optical

opal



transparent



transparent  
prismatic



satin



custom



### Ceiling Mount

direct



perpendicular



conical



remote driver



custom

