



# CIRCUS round S500 v2 1-10V 100-277V

ver. 20200804\_Rev\_1

year: 2015  
code: 2730311S20000  
type: hanging lamp  
application: indoor



**Technical drawing**  
Size ref. image mm - inch



Technical data	
Light source	LED
Circuit structure	LED strip
Light emission direction	diffused
Power	37 W
Source lumens	5180 lm
Source efficacy	140 lm/W
Consumption	42 W
Delivered lumens	3259 lm
Luminaire efficacy	78 lm/W
Secondary	24 V
Colour temperature	3000 K / variants page 2
Colour rendering index	80 CRI / variants page 2
Standard Deviation of Colour Matching	3 SDCM
Energy class	A
Safety class	I
Degree of protection	IP 20
Direct mounting on normally flammable surfaces	●
Operating temperature	+10° / +40°
CE	●
UL	●
Optional	
Emergency mode	○
Motion sensor	○
Directional	○
Packing	
Net weight	
Packaging 1	L610 x W610 x h19 mm / 4.9 kg
Packaging 2	
Packaging 3	
Packaging 4	
Packaging 5	

Structure	
Material	aluminium
Finish	white / variants page 2
Diffuser	
Material	polycarbonate
Finish	opal / variants page 2
Canopy	
Size	200 mm - 7" 7/8 inch
Height	57 mm - 2" 1/4 inch
Ceiling mount	perpendicular / variants page 2

Electronics / Driver	
Included	Yes
Quantity	1
Voltage	100-277V 50/60 Hz

Dimmable	
ON/OFF	●
PUSH	●
0-10V	●
1-10V	●
CUT PHASE	●
Bluetooth	●
DALI	●

Hanging cables	
Stainless steel cables standard length (custom available)	2000 mm / 78" 3/4
Electric cable standard length (custom available)	2500 mm/100"

Warranty	
Duration	2 years

# CIRCUS round S500 v2 1-10V 100-277V

ver. 20200804\_Rev\_1

year: **2015**

code: **2730311S20000**

type: **hanging lamp**

application: **indoor**

## Available variants

### Colour temperature

2700 k



3000 k



3500 k



4000 k



custom



### Colour rendering index

CRI 80



CRI 90



CRI 95



custom



### Structure finish

gold / brass



matt white



matt black



embossed white



embossed black



custom



### Diffuser / Optical

opal



transparent



transparent  
prismatic



satin



custom



### Ceiling Mount

direct



perpendicular



conical



remote driver



custom

