

# CIRCUS upright POWER 0\_1-10V 110V


ver. 20200404\_Rev\_0

year: 2015

code: 1732502A20150

type: surface lamp


application: indoor



## Technical drawing

Size

ref. image mm - inch



## Technical data

Light source	LED
Circuit structure	LED module G2
Light emission direction	indirect
Power	49 W
Source lumens	7590 lm
Source efficacy	155 lm/W
Consumption	58 W
Delivered lumens	7380 lm
Luminaire efficacy	127 lm/W
Secondary	1400mA
Colour temperature	3000 K / variants page 2
Colour rendering index	90 CRI
Standard Deviation of Colour Matching	3 SDCM
Energy class	A
Safety class	I
Degree of protection	IP 20
Direct mounting on normally flammable surfaces	●
Operating temperature	+10° / +40°
CE	●
UL	○
<b>Optional</b>	
Emergency mode	○
Motion sensor	○
Directional	○

## Packing

Net weight
Packaging 1
Packaging 2
Packaging 3
Packaging 4
Packaging 5

## Structure

Material	aluminium
Finish	white / variants page 2

## Diffuser

Material	pmma
Finish	satin / variants page 2

## Electronics / Driver

Included	Yes
Quantity	1
Voltage	100-277V 50/60 Hz

## Dimmable



## Hanging cables

Stainless steel cables standard length (custom available)	○
Electric cable standard length (custom available)	-

## Warranty

Duration	2 years
----------	---------

# CIRCUS uplight POWER 0\_1-10V 110V

ver. 20200404\_Rev\_0

year: **2015**

code: **1732502A20150**

type: **surface lamp**

application: **indoor**

## Available variants

### Colour temperature

3000 k



4000 k



custom



### Colour rendering index

CRI 80



CRI 90



CRI 95



custom



### Structure finish

matt white



matt black



embossed white



embossed black



custom



### Diffuser / Optical

opal



transparent



transparent  
prismatic



satin



custom

