



# CIRCUS upright BASIC ON-OFF 220V

ver. 20200404\_Rev\_0

year: **2015**  
code: **1732501E00150**  
type: **surface lamp**  
application: **indoor**



**Technical drawing**  
Size ref. image mm - inch



Technical data	
Light source	LED
Circuit structure	LED module G2
Light emission direction	indirect
Power	17 W
Source lumens	2780 lm
Source efficacy	164 lm/W
Consumption	25 W
Delivered lumens	2440 lm
Luminaire efficacy	99 lm/W
Secondary	500mA
Colour temperature	3000 K / variants page 2
Colour rendering index	90 CRI
Standard Deviation of Colour Matching	3 SDCM
Energy class	A
Safety class	I
Degree of protection	IP 20
Direct mounting on normally flammable surfaces	●
Operating temperature	+10° / +40°
CE	●
UL	○
Optional	
Emergency mode	○
Motion sensor	○
Directional	○

Packing	
Net weight	
Packaging 1	
Packaging 2	
Packaging 3	
Packaging 4	
Packaging 5	

Structure	
Material	aluminium
Finish	white / variants page 2
Diffuser	
Material	pmma
Finish	satin / variants page 2
Electronics / Driver	
Included	Yes
Quantity	1
Voltage	100-277V 50/60 Hz
Dimmable	
ON/OFF	●
PUSH	○
0-10V	○
1-10V	○
CUT PHASE	○
Bluetooth	○
DALI	○
Hanging cables	
Stainless steel cables standard length (custom available)	○
Electric cable standard length (custom available)	-
Warranty	
Duration	2 years

# CIRCUS upright BASIC ON-OFF 220V

ver. 20200404\_Rev\_0

year: **2015**

code: **1732501E00150**

type: **surface lamp**

application: **indoor**

## Available variants

### Colour temperature

3000 k



4000 k



custom



### Colour rendering index

CRI 80



CRI 90



CRI 95



custom



### Structure finish

matt white



matt black



embossed white



embossed black



custom



### Diffuser / Optical

opal



transparent



transparent  
prismatic



satin



custom

