


CIRCUS round vertical S500 v2 1-10V 100-277V


ver. 20200804_Rev_1

year: **2022**
code: **2730372S20000**
type: **hanging lamp**
application: **indoor**



Technical drawing

Size ref. image mm - inch



Technical data	
Light source	LED
Circuit structure	LED strip
Light emission direction	diffused
Power	37 W
Source lumens	5180 lm
Source efficacy	140 lm/W
Consumption	42 W
Delivered lumens	3259 lm
Luminaire efficacy	78 lm/W
Secondary	24 V
Colour temperature	3000 K / variants page 2
Colour rendering index	80 CRI / variants page 2
Standard Deviation of Colour Matching	3 SDCM
Energy class	A
Safety class	I
Degree of protection	IP 20
Direct mounting on normally flammable surfaces	●
Operating temperature	+10° / +40°
CE	●
UL	○
Optional	
Emergency mode	○
Motion sensor	○
Directional	○
Packing	
Net weight	
Packaging 1	L610 x W610 x h19 mm / 4.9 kg
Packaging 2	
Packaging 3	
Packaging 4	
Packaging 5	

Structure	
Material	aluminium
Finish	white / variants page 2
Diffuser	
Material	polycarbonate
Finish	opal / variants page 2
Canopy	
Size	200 mm - 7" 7/8 inch
Height	57 mm - 2" 1/4 inch
Ceiling mount	perpendicular / variants page 2

Electronics / Driver	
Included	Yes
Quantity	1
Voltage	100-277V 50/60 Hz

Dimmable	
ON/OFF	○
PUSH	○
0-10V	○
1-10V	●
CUT PHASE	○
Bluetooth	○
DALI	○

Hanging cables	
Stainless steel cables standard length (custom available)	2000 mm / 78" 3/4
Electric cable standard length (custom available)	2500 mm/100"

Warranty	
Duration	2 years

CIRCUS round vertical S500 v2 1-10V 100-277V

ver. 20200804_Rev_1

year: **2022**

code: **2730372S20000**

type: **hanging lamp**

application: **indoor**

Available variants

Colour temperature

2700 k



3000 k



3500 k



4000 k



custom



Colour rendering index

CRI 80



CRI 90



CRI 95



custom



Structure finish

gold / brass



matt white



matt black



embossed white



embossed black



custom



Diffuser / Optical

opal



transparent



transparent
prismatic



satin



custom



Ceiling Mount

direct



perpendicular



remote driver



custom

