



# CYL model 75 0-10V 100-240V


ver. 20200404\_Rev\_0

year: **2022**  
code: **2661004U20161**  
type: **projector**  
application: **indoor**



## Technical drawing

Size ref. image mm - inch



Technical data	
Light source	LED
Circuit structure	COB LED
Light emission direction	direct
Power	17 W
Source lumens	1900 lm
Source efficacy	112 lm/W
Consumption	17 W
Delivered lumens	1615 lm
Luminaire efficacy	95 lm/W
Secondary	500mA
Colour temperature	3000 K / variants page 2
Colour rendering index	95 CRI
Standard Deviation of Colour Matching	3
Energy class	x
Safety class	I
Degree of protection	IP 20
Direct mounting on normally flammable surfaces	●
Operating temperature	+10° / +40°
CE	●
UL	○
Optional	
Emergency mode	○
Motion sensor	○
Directional	●

Packing	
Net weight	
Packaging 1	
Packaging 2	
Packaging 3	
Packaging 4	
Packaging 5	

Structure	
Material	aluminium
Finish	white / variants page 2

Diffuser	
Material	pmma
Finish	lens beam 12°

Electronics / Driver	
Included	Yes
Quantity	1
Voltage	100-240V 50/60 Hz

Dimmable	
ON/OFF	○
PUSH	○
0-10V	●
1-10V	○
CUT PHASE	○
Bluetooth	○
DALI	○

Hanging cables	
Stainless steel cables standard length (custom available)	○
Electric cable standard length (custom available)	○

Warranty	
Duration	2 years