



# CYL model 60 0-10V TRACK 48V

ver. 20200404\_Rev\_0

year: **2022**  
code: **2661003T20161**  
type: **projector**  
application: **indoor**



**Technical drawing**  
Size ref. image mm - inch



| Technical data                                 |                          |
|--|--------------------------|
| Light source                                   | LED                      |
| Circuit structure                              | COB LED                  |
| Light emission direction                       | direct                   |
| Power  | 12 W                     |
| Source lumens                                  | 1300 lm                  |
| Source efficacy                                | 108 lm/W                 |
| Consumption                                    | 12 W                     |
| Delivered lumens                               | 1105 lm                  |
| Luminaire efficacy                             | 92 lm/W                  |
| Secondary                                      | 350mA                    |
| Colour temperature                             | 3000 K / variants page 2 |
| Colour rendering index                         | 95 CRI                   |
| Standard Deviation of Colour Matching          | 3                        |
| Energy class                                   | x                        |
| Safety class                                   | III                      |
| Degree of protection                           | IP 20                    |
| Direct mounting on normally flammable surfaces | ●                        |
| Operating temperature                          | +10° / +40°              |
| CE   | ●                        |
| UL   | ○                        |
| Optional                                       |                          |
| Emergency mode                                 | ○                        |
| Motion sensor                                  | ○                        |
| Directional                                    | ●                        |

| Packing     |  |
|-------------|--|
| Net weight  |  |
| Packaging 1 |  |
| Packaging 2 |  |
| Packaging 3 |  |
| Packaging 4 |  |
| Packaging 5 |  |

| Structure   |                         |
|---|-------------------------|
| Material  | aluminium               |
| Finish  | white / variants page 2 |
| Diffuser  |                         |
| Material  | pmma                    |
| Finish  | lens beam 15°           |
| Electronics / Driver                                      |                         |
| Included  | Yes                     |
| Quantity  | 1                       |
| Voltage   | 48V                     |
| Dimmable  |                         |
| ON/OFF  | ○                       |
| PUSH  | ○                       |
| 0-10V   | ●                       |
| 1-10V   | ○                       |
| CUT PHASE   | ○                       |
| Bluetooth   | ○                       |
| DALI  | ○                       |
| Hanging cables  |                         |
| Stainless steel cables standard length (custom available) | ○                       |
| Electric cable standard length (custom available)         | ○                       |
| Warranty  |                         |
| Duration  | 2 years                 |