




CYL model 45 DALI2 100-240V

ver. 20200404_Rev_0

year: **2022**
code: **2661002U10161**
type: **projector**
application: **indoor**



Technical drawing
Size ref. image mm - inch



Technical data

Light source	LED
Circuit structure	COB LED
Light emission direction	direct
Power	7 W
Source lumens	720 lm
Source efficacy	103 lm/W
Consumption	7 W
Delivered lumens	612 lm
Luminaire efficacy	87 lm/W
Secondary	200mA
Colour temperature	3000 K / variants page 2
Colour rendering index	95 CRI
Standard Deviation of Colour Matching	3
Energy class	x
Safety class	I
Degree of protection	IP 20
Direct mounting on normally flammable surfaces	●
Operating temperature	+10° / +40°
CE	●
UL	○
Optional	
Emergency mode	○
Motion sensor	○
Directional	●

Packing

Net weight
Packaging 1
Packaging 2
Packaging 3
Packaging 4
Packaging 5

Structure

Material	aluminium
Finish	white / variants page 2

Diffuser

Material	pmma
Finish	lens beam 18°

Electronics / Driver

Included	Yes
Quantity	1
Voltage	100-240V 50/60 Hz

Dimmable



Hanging cables

Stainless steel cables standard length (custom available)	○
Electric cable standard length (custom available)	○

Warranty

Duration	2 years
----------	---------