


# LUNA S1250 HORIZONTAL DOWNWARD DALI 220V


ver. 20200404\_Rev\_0

year: **2021**  
code: **2670311E10000**  
type: **hanging lamp**  
application: **indoor**



## Technical drawing

Size ref. image mm - inch



Technical data	
Light source	LED
Circuit structure	LED strip
Light emission direction	direct
Power	78 W
Source lumens	10920 lm
Source efficacy	140 lm/W
Consumption	84 W
Delivered lumens	8935 lm
Luminaire efficacy	106 lm/W
Secondary	24 V
Colour temperature	3000 K / variants page 2
Colour rendering index	80 CRI / variants page 2
Standard Deviation of Colour Matching	3 SDCM
Energy class	A
Safety class	II
Degree of protection	IP 20
Direct mounting on normally flammable surfaces	●
Operating temperature	+10° / +40°
CE	●
UL	○
Optional	
Emergency mode	○
Motion sensor	○
Directional	○

Packing	
Net weight	
Packaging 1	
Packaging 2	
Packaging 3	
Packaging 4	
Packaging 5	

Structure	
Material	aluminium
Finish	white / variants page 2
Diffuser	
Material	polymer stretch
Finish	opal / variants page 2
Electronics / Driver	
Included	Yes
Quantity	1
Voltage	220-240V 50/60 Hz
Dimmable	
Hanging cables	
Stainless steel cables standard length (custom available)	2000 mm / 78" 3/4
Electric cable standard length (custom available)	2500 mm/100"
Warranty	
Duration	2 years

# LUNA S1250 HORIZONTAL DOWNWARD DALI 220V

ver. 20200404\_Rev\_0

year: **2021**

code: **2670311E10000**

type: **hanging lamp**

application: **indoor**

## Available variants

### Colour temperature

2700 k



3000 k



3500 k



4000 k



custom



### Colour rendering index

CRI 80



CRI 90



CRI 95



custom



### Structure finish

gold / brass



matt white



matt black



embossed white



embossed black



custom



### Diffuser / Optical

opal



custom



### Ceiling Mount

perpendicular



remote driver



custom

