



LUNA C900 0-10V 110V

ver. 20200404_Rev_0

year: **2022**
code: **2670201A20000**
type: **ceiling lamp**
application: **indoor**



Technical drawing
Size ref. image mm - inch



Technical data	
Light source	LED
Circuit structure	LED strip
Light emission direction	direct
Power	69 W
Source lumens	9660 lm
Source efficacy	140 lm/W
Consumption	74 W
Delivered lumens	6406 lm
Luminaire efficacy	87 lm/W
Secondary	24 V
Colour temperature	3000 K / variants page 2
Colour rendering index	80 CRI / variants page 2
Standard Deviation of Colour Matching	3 SDCM
Energy class	A
Safety class	II
Degree of protection	IP 20
Direct mounting on normally flammable surfaces	●
Operating temperature	+10° / +40°
CE	●
UL	○
Optional	
Emergency mode	○
Motion sensor	○
Directional	○

Packing	
Net weight	
Packaging 1	
Packaging 2	
Packaging 3	
Packaging 4	
Packaging 5	

Structure	
Material	aluminium
Finish	white / variants page 2
Diffuser	
Material	polymer stretch
Finish	opal / variants page 2
Electronics / Driver	
Included	Yes
Quantity	1
Voltage	100-120V 60 Hz
Dimmable	
ON/OFF	○
PUSH	○
0-10V	●
1-10V	○
CUT PHASE	○
Bluetooth	○
DALI	○
Hanging cables	
Stainless steel cables standard length (custom available)	-
Electric cable standard length (custom available)	-
Warranty	
Duration	2 years

LUNA C900 0-10V 110V

ver. 20200404_Rev_0

year: **2022**

code: **2670201A20000**

type: **ceiling lamp**

application: **indoor**

Available variants

Colour temperature

2700 k



3000 k



3500 k



4000 k



custom



Colour rendering index

CRI 80



CRI 90



CRI 95



custom



Structure finish

gold / brass



matt white



matt black



embossed white



embossed black



custom



Diffuser / Optical

opal



custom



Ceiling Mount

remote driver



custom

