


LUNA S430 HORIZONTAL UP-DOWN DALI 220V

ver. 20200404_Rev_0



year: **2021**
code: **2670305E10000**
type: **hanging lamp**
application: **indoor**



Technical drawing

Size

ref. image mm - inch



Technical data

Light source	LED
Circuit structure	LED strip
Light emission direction	direct and indirect
Power	32 W
Source lumens	4480 lm
Source efficacy	140 lm/W
Consumption	36 W
Delivered lumens	2069 lm
Luminaire efficacy	57 lm/W
Secondary	24 V
Colour temperature	3000 K / variants page 2
Colour rendering index	80 CRI / variants page 2
Standard Deviation of Colour Matching	3 SDCM
Energy class	A
Safety class	II
Degree of protection	IP 20
Direct mounting on normally flammable surfaces	●
Operating temperature	+10° / +40°
CE	●
UL	○
Optional	
Emergency mode	○
Motion sensor	○
Directional	○

Packing

Net weight
Packaging 1
Packaging 2
Packaging 3
Packaging 4
Packaging 5

Structure

Material	aluminium
Finish	white / variants page 2

Diffuser

Material	polymer stretch
Finish	opal / variants page 2

Electronics / Driver

Included	Yes
Quantity	1
Voltage	220-240V 50/60 Hz

Dimmable



Hanging cables

Stainless steel cables standard length (custom available)	2000 mm / 78" 3/4
Electric cable standard length (custom available)	2500 mm/100"

Warranty

Duration	2 years
----------	---------

LUNA S430 HORIZONTAL UP-DOWN DALI 220V

ver. 20200404_Rev_0

year: **2021**

code: **2670305E10000**

type: **hanging lamp**

application: **indoor**

Available variants

Colour temperature

2700 k



3000 k



3500 k



4000 k



custom



Colour rendering index

CRI 80



CRI 90



CRI 95



custom



Structure finish

gold / brass



matt white



matt black



embossed white



embossed black



custom



Diffuser / Optical

opal



custom



Ceiling Mount

perpendicular



remote driver



custom

